

TENDA AC5 v3 white AC1200 wireless dual band ruter

TENDA AC5 v3 white AC1200 wireless dual band ruter 2.4+5GHz, 1W/3L 10/100, 1Ghz cpu, 4x5dBi , 9v/1

Šifra: 18850
Kategorija proizvoda: Ruteri
Proizvođač: Tenda

Cena: **2.881,00** din.

AC5 is an AC1200 dual band WiFi router, designed for medium-sized apartment with a 100Mbps fiber access. It provides WiFi speed up to 1167 Mbps (5GHz: 867Mbps and 2.4GHz: 300Mbps). Adopted the integrated dual-band technology, combining 2.4GHz and 5GHz signals under one WiFi name. The faster band would be allocated to your devices automatically by our dynamic optimization system. Meanwhile, featured with 4*6dBi high-gain antennas and equipped with a 28nm high performance CPU, it brings a better internet experience. AC5 supports IPv6 protocol, it can reduce the data transmission time and minimize the lag. Furthermore, the remote management function by the Tenda WiFi App provides the easiest way to manage AC5. Standard&Protocol IEEE802.3,IEEE802.3u,IEEE802.3ab Interface 1*10/100Mbps WAN port 3*10/100Mbps LAN ports Antenna 4*6dBi external high-gain antennas Button 1*WPS/Reset button Power Input:AC 100-240V—50/60Hz Output:DC 9V 1A LED indicator 1*LED Dimension 200x127x33.6mm(L*W*H) Wireless Standards IEEE 802.11ac/a/n @5GHz IEEE 802.11b/g/n @2.4GHz Data Rate 2.4GHz: 300Mbps 5GHz: 867Mbps Frequency 2.400 – 2.4835 GHz 5.150 – 5.250 GHz Wireless Security WPA-PSK/WPA2-PSK, WPA/WPA2 Wireless Security : Enable /Disable Internet Connection Type PPPoE, Dynamic IP, Static IP Support automatic access detection Supports broadband account automatic transfer Operating Mode Wireless Router Mode AP Mode Universal Repeater mode WISP Mode DHCP DHCP Server DHCP Client List DHCP Reservation Virtual ServerPort Forwarding DMZ Host UPnP Security Client Filter(supports black list and white list) Parental Control(supports black list and white list) Remote Web Management Firewall Forbid WAN PING from internet DDNS Support DynDNS, 88ip Other featuresSupport IPv6 Broadband management MAC address clone Static Routing System Log Backup & Restore configurations Firmware upgrade from local Temperature Operating Temperature: 0? ~ 40? Storage Temperature: -40? ~ 70?. Humidity Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing. Default SettingsDefault Access: tendawifi.com or http://192.168.0.1 Certification CE,RoHS,FCC,CCC,SRRC, EIRP Power (Max.)2.400 – 2.4835 GHz:19.85 dBm (EIRP) 5.150 – 5.250 GHz:22.96dBm (EIRP) Package Content Wireless Router*1 Ethernet Cable*1 Power Adapter*1 Installation Guide*1