



## Gigabyte Matična ploča AM4 B550 AORUS ELITE V2

Šifra: 47699

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **16.883,00** din.



### Tip procesora:

AMD  
AMD&reg; AM4  
AMD&reg; B550  
ATX  
AMD Ryzen™ 5000 Series  
Ryzen™ 5000 G-Series Ryzen™  
4000 G-Series and Ryzen™ 3000  
Series Processors  
DDR4  
Maksimalna ukupna memorija:  
128GB Podržane memorije:  
2.133MHz, 2.400MHz, 2.667MHz,  
2.933MHz, 3.200MHz, 3.300Mhz  
(O.C.), 3.333Mhz (O.C.),  
3.400Mhz (O.C.), 3.466Mhz  
(O.C.), 3.600Mhz (O.C.),  
3.733Mhz (O.C.), 3.800Mhz  
(O.C.), 3.866Mhz (O.C.),  
4.000Mhz (O.C.), 4.400Mhz  
(O.C.), 4.733Mhz (O.C.)  
1 x PCI Express x16 slot  
(PCIEX16), integrated in the  
CPU: - AMD Ryzen™ 5000 Series  
and Ryzen™ 3000 Series  
Processors support PCIe 4.0 x16  
mode - AMD Ryzen™ Ryzen™  
5000 G-Series and Ryzen™ 4000  
G-Series Processors support PCIe  
3.0 x16 mode \* For optimum  
performance, if only one PCI  
Express graphics card is to be  
installed, be sure to install it in  
the PCIEX16 slot. 1 x PCI Express  
x16 slot (PCIEX2), integrated in  
the Chipset: - Supporting PCIe  
3.0 x2 mode 1 x PCI Express x16  
slot (PCIEX1\_2), integrated in the  
Chipset: - Supporting PCIe 3.0 x1  
mode 1 x PCI Express x1 slot  
(PCIEX1\_1), integrated in the  
Chipset: - Supporting PCIe 3.0 x1

### Podnožje:

Čipset:  
Format ploče:  
Podržani procesori:  
Podržana memorija:

### Memorija:

Slotovi za proširenje:

mode

Storage:	1 x M.2 connector (M2A_CPU), integrated in the CPU, supporting Socket 3, M key, type 22422260228022110 SSDs: - AMD Ryzen™ 5000 Series and Ryzen™ 3000 Series Processors support SATA and PCIe 4.0 x4x2 SSDs - AMD Ryzen™ Ryzen™ 5000 G-Series and Ryzen™ 4000 G-Series Processors support SATA and PCIe 3.0 x4x2 SSDs 1 x M.2 connector (M2B_SB), integrated in the Chipset, supporting Socket 3, M key, type 22422260228022110 SSDs: - Supporting SATA and PCIe 3.0 x4x2 SSDs 4 x SATA 6Gbs connectors, integrated in the Chipset: - Support for RAID 0, RAID 1, and RAID 10
Mrežna karta:	
Zvučna karta:	Realtek® ALC1200 codec High Definition Audio 245.17.1-channel Support for SPDIF Out
USB:	Chipset: 2 x USB 3.2 Gen 2 Type-A ports (red) on the back panel 2 x USB 3.2 Gen 1 ports on the back panel Chipset: 1 x USB Type-C™ port with USB 3.2 Gen 1 support) available through the internal USB 3.2 Gen 1 headers 2 x USB 2.01.1 ports 1 x USB 3.2 Gen 1 port on the back panel 2 optical SPDIF Out ports available through the internal USB header 2 x USB 2.01.1 ports on the back panel Chipset+USB 2.0 Hub: 4 x USB 2.01.1 ports available through the internal USB headers
Konektori na zadnjoj strani:	1 x DisplayPort 1 x HDMI port 2 x USB 3.2 Gen 1 ports (red) 2 x USB 3.2 Gen 1 ports (red) 2 x USB 2.01.1 ports 1 x USB 3.2 Gen 1 port on the back panel 2 optical SPDIF Out ports available through the internal USB header 2 x USB 2.01.1 ports on the back panel Chipset+USB 2.0 Hub: 4 x USB 2.01.1 ports available through the internal USB headers
Interni konektori:	1 x 24-pin ATX main power connector 1 x 8-pin ATX 12V power connector 2 x M.2 Socket 3 connectors 4 x SATA 6Gbs connectors 1 x CPU fan header 1 x water cooling CPU fan header 3 x system fan headers 1 x CPU cooler LED strip RGB LED-strip header 2 x addressable LED-strip headers 2 x RGB LED strip headers 2 x RGB LED strip headers 2 x M.2 BIOS 2.7, headers 1 x front panel header 1 x front panel audio header 1 x USB Type-C™ port, with USB 3.2 Gen 1 support 1 x USB 3.2 Gen 1 header 2 x USB 2.01.1 headers 1 x Trusted Platform Module (TPM) header (2x6 pin, for the GC-TPM2.0_S module only) 1 x Clear CMOS jumper
Bios:	licensed AMI UEFI BIOS with 1.0, BIOS 2.7, WMM 2.0, 5M BIOS

